

MAX-PLANCK-GESELLSCHAFT

Quality assurance and quality control (QA/QC) of the production of thin-gap RPCs for the ATLAS phase 2 upgrade

—
Davide Costa

on behalf of the MPP ATLAS Muon Group



Max-Planck-Institut für Physik
(Werner-Heisenberg-Institut)

DPG-Frühjahrstagung 2025

Göttingen – 31st March - 4th April 2025



FSP ATLAS
Erforschung von
Universum und Materie


RPCs for the ATLAS Muon System Upgrade



Installation of ~1000 1mm-gap RPCs in the inner layer of the barrel to maximize the efficiency and geometrical acceptance of the muon trigger.

Challenges:

- **Very tight space constraints:**
only 60 mm in radial space available for the system.
- **Higher rate capability:**
make up for loss in efficiency of legacy RPC system.
- **Required longevity:**
>10 years of operation at HL-LHC till 2040.




New production and certification facilities for ~300/1000 thin-gap RPCs have been established at MPI, with technology transfer to German industry partners.



New generation of ATLAS 1mm-gap RPCs

schematic drawing of RPC singlet



- **Electrode material:**
phenolic high-pressure laminate ($\rho_V = 10^{10} \Omega \times \text{cm}$)
- **Gas mixture:**
 $\text{C}_2\text{H}_2\text{F}_4 / \text{iso-C}_4\text{H}_{10} / \text{SF}_6$ (94.7 / 5 / 0.3)
- **Rate capability and longevity:**
up to 1 kHz/cm^2 for 10 years of HL-LHC

Solutions:


- **Reduced bakelite thickness:**
 - Less voltage loss in bakelite → improve the rate capability, larger induced signals.
- **Reduced gap size:**
 - Less charge produced per event → improve longevity, rate capability.
- **New generation FE electronic:**
 - Very low-noise and very sensitive front-end electronics to compensate the lost gas amplification.

Assembly Procedure


The 1mm-gap RPCs production involve several stages:

- 1. Electrode production, installation of HV contacts, and lamination.**
2. Gas gap production.
3. Gas pipe installation, edge sealing, sticker application.
4. Linseed oil coating.


graphite coating of the HPL electrodes



laminating press machine





HPL electrode after lamination



Assembly Procedure

The 1mm-gap RPCs production involve several stages:



1. Electrode production, installation of HV contacts, and lamination.
- 2. Gas gap production.**
3. Gas pipe installation, edge sealing, sticker application.
4. Linseed oil coating.



Assembly Procedure

The 1mm-gap RPCs production involve several stages:


1. Electrode production, installation of HV contacts, and lamination.
- 2. Gas gap production.**
3. Gas pipe installation, edge sealing, sticker application.
4. Linseed oil coating.



Assembly Procedure

The 1mm-gap RPCs production involve several stages:


1. Electrode production, installation of HV contacts, and lamination.
2. Gas gap production.
- 3. Gas pipe installation, edge sealing, sticker application.**
4. Linseed oil coating.



Assembly Procedure

The 1mm-gap RPCs production involve several stages:

1. Electrode production, installation of HV contacts, and lamination.
2. Gas gap production.
3. Gas pipe installation, edge sealing, sticker application.
4. **Linseed oil coating.**




schematic drawing of the oiling station

Assembly Procedure

The 1mm-gap RPCs production involve several stages:

1. Electrode production, installation of HV contacts, and lamination.
2. Gas gap production.
3. Gas pipe installation, edge sealing, sticker application.
4. **Linseed oil coating.**


The mock-up volume will later be opened to verify the quality of the coating (fully polymerised, uniform, clean)



schematic drawing of the polymerisation station

Quality Control Flowchart

An extensive **Quality Assurance and Quality Control (QA/QC)** program has been established to guarantee **high quality and reliability** of the **gas volume production** to meet the stringent requirements of ATLAS



Materials Acceptance Tests

QA/QC step 1: HPL production test

- Visual inspection of surface, volume resistivity meas., thickness meas.

QA/QC step 2: Electrode production test

- Visual inspection and surface resistivity meas. of the graphite coating.
- Test of absence of bubbles between the insulating PET foil and the graphite coating.



visual inspection





volume resistivity meas.



thickness meas.

Objective:

The combined leak rate of the gas volume and gas system is measured by monitoring the drop of internal pressure in order to ensure that gas tightness requirements are met.



Methodology:

- Chamber is over-pressurized at **3 mbar** (3x operating overpressure for ATLAS RPCs).
- Monitor the drop over **10 minutes**, using a precision pressure gauge.
- Setup is completely automated, improving reliability and production efficiency.
- The combined acceptance limit for the gas volume and system is a leak rate of -9.7×10^{-4} mbar \times l/s.

Gas Gap Mechanical Rigidity Test

Objective:

Ensure gas volume integrity by detecting **popped-up spacers** caused by **insufficient adhesive bonding** or **improper handling** during fabrication process.



Methodology:

- Initial Test:** A **laser scan planarity test** is conducted to assess the **flatness** of the gas volume at **atmospheric pressure**.
- Pressurized Test:** The gas volume is then **pressurized to 3 mbar above atmospheric pressure**, and the **laser scan planarity test** is repeated.

Analysis:

Residuals are calculated by comparing the **laser scans** at **atmospheric** and **pressurized conditions** to identify any **discrepancies** indicating **popped-up spacers**.

Gas channels



Mock-up gas volume opening

The mock-up is an accurate representation of the status of the full-scale volume, in terms of detector components, materials, and quality of the coating.

○ Expected visual inspection results:

- The oil coating is applied uniformly across all surfaces.
- The linseed oil has fully polymerized on both HPL plates.
- Minimal dust / debris should be present in the coating.

○ Scratch resistance:

- A 10 mm blade, held at 45°, applying 1 N of force, scrapes the coating for a length of 100 mm.
- No oil residue should be left on the blade, and no damage should be visible on the coating.




Leakage Current Measurement

Objective:

Measure the leakage current within the HPL electrodes of the gas volume to ensure proper insulation and minimal leakage.


Methodology:

1. The HPL electrodes are subjected to the same voltage. This allows us to perform the test in air
2. A copper-coated teflon bar, grounded through a 100 kΩ resistor, is brought into contact with the long side of the gas gap under test. The presence of a layer of conductive rubber ensures a good electrical contact across the whole length.
3. The leakage current is monitored through the voltage drop across the resistor.



Analysis:

The gas volume passes the test if the leakage current does not exceed 200nA at the maximum applied voltage of 8 kV on both HPL electrodes.



Volt-Amperometric Characteristic Test

Objective:

Characterize the **gas volume** by evaluating the **current flow** through the **gas gap** under different **voltages** with the **standard ATLAS RPC gas mixture** (94.7% $C_2H_2F_4$: 5% $i-C_4H_{10}$: 0.3% SF_6).

Methodology:


1. The **voltage scan** is conducted by gradually **increasing** the **applied voltage** in **200 V increments** up to **4 kV**, followed by **100 V increments** up to **6.2 kV**.
1. The **current** flowing through the **gas gap** is measured via a **100 k Ω resistor** connected in series with the device.
1. The **applied voltage** V_{app} is rescaled to calculate the **effective voltage** V_{eff} using the equation: $V_{eff} = V_{app} \times (P_0 / P) \times (T / T_0)$, where $P_0=1010$ mbar and $T_0=293$ K.

Analysis:

Acceptance Limits:

1. **Maximum current** of **3 μA** at **6.1 kV** after subtracting **ohmic contribution**.
1. **Maximum current** of **1 μA** at **3.5 kV**.

Ohmic contribution is determined using a **linear fit** in the range **[0, 3] kV**.






Long-Term Stability Test

Objective:


Ensure long-term gas volume stability by continuously monitoring the gas gap current over time with the standard ATLAS RPC gas mixture.

Methodology:




1. The gas gap current is continuously monitored over time at applied voltages of 5.0 kV, 5.4 kV, and 5.8 kV, with each conditioning step lasting 48 hours.
2. Real-time voltage correction to compensate for environmental parameters.
3. The volt-ampere characteristic curves are measured at both the beginning and the end of the conditioning period.



QA/QC summary



- To date, six real-scale RPC gas volumes have been successfully assembled: two at MIRION, two at PTS, and two at MPI.
- All real-scale gas volumes produced by MPI and German companies fully meet the stringent acceptance requirements.
- QA/QC tests have been, where possible, automated, with plans to build independent test stands, fully integrated with the required equipment, on track to be completed before the start of production in the Summer of 2025.
- A real-scale gas volume from each production site has been selected for final longevity certification at CERN.





Thank you for your attention



Extras

RPCs for the ATLAS Muon System Upgrade




Installation of ~ 1000 1mm-gap RPCs in the inner layer of the to maximize the efficiency and geometrical acceptance of the muon trigger.


Challenges:

- **Very tight space constraints:**
only 60 mm in radial space available for the system.
- **Higher rate capability:**
make up for loss in efficiency of legacy RPC system.
- **Required longevity:**
>10 years of operation at HL-LHC till 2040.

The challenge is to build a new generation of 1mm-gap RPCs with **higher rate capability** and **longevity**.



efficiency drops due to the uninstrumented detector regions



RPCs for the ATLAS Muon System Upgrade





Installation of ~ 1000 1mm-gap RPCs in the inner layer of the to maximize the efficiency and geometrical acceptance of the muon trigger.

Challenges:

- **Very tight space constraints:**
only 60 mm in radial space available for the system.
- **Higher rate capability:**
make up for loss in efficiency of legacy RPC system.
- **Required longevity:**
>10 years of operation at HL-LHC till 2040.

The challenge is to build a new generation of 1mm-gap RPCs with **higher rate capability** and **longevity**.



Establishing New RPC Production Facilities




- The MPI team leads the industrialization of 1mm-gap RPC detector technology for the ATLAS Muon Spectrometer upgrade, preparing for the HL-LHC era and future collider projects.
- ~300/1000 RPCs required for the ATLAS Muon Spectrometer upgrade will be produced at the MPI in collaboration with industrial partners.
- Successful technology transfer to industrial manufacturers has enabled large-scale RPC production that meets the stringent ATLAS standards.
- Dedicated facilities for the construction and certification of 1mm-gap RPCs have been established at:



MIRION
TECHNOLOGIES

PTS
Maschinenbau

Quality Control Flowchart (pre-production)





Long-Term Partnership with Industry



A fully established production site at MPI, enabling reliable and scalable manufacturing of PRC detectors in partnership with industry.

- Multiple prototype iterations produced at MPI to validate and refine manufacturing steps.
- Lessons learned integrated back into processes, ensuring robust and reliable production workflows.
- Implementation of rigorous industrial-level quality assurance and control measures.
- Extensive collaboration with industry to gradually mature production capabilities.

Deep understanding of RPC technology leading to improvements in detector design, prioritizing on reliable manufacturing, rigorous QA/QC, and backed by dedicated in-house engineering expertise.




Assembly Procedure


The 1mm-gap RPCs production involve several stages:

- Production step 1: **HPL electrode production**
 1. **Graphite coating** on surface of the **HPL electrodes** using a **silk-screen technique** in industry.
 - Mesh size: 90 threads/cm and drying process at 105 °C for 1h.
 2. Installation of the **high-voltage** and **ground contact**.
 - Epoxy silver glue: E-Solder® 3025; curing time: 24-36 h at 25 °C.
 3. **Laminating** of the **insulating Polyethylene Terephthalate (PET) film** onto the **HPL electrodes**.
 - Laminating Perfex gloss PET-EVA foil (190 μm PET + 80 μm EVA).
 - Roll lamination at 105 °C under pressure at ~3 m/min.


graphite coating of the HPL electrodes



laminating press machine



HPL electrode after lamination



Assembly Procedure



- Production step 2: Gas gap production

Component Preparation

1. Thoroughly cleaning of the polycarbonate spacers and lateral profiles with isopropanol.
2. Placing components onto a Teflon gluing jig, secured by a vacuum system during adhesive application

Adhesive Application

3. Using an automated gluing dispenser integrated with an X-Y-Z robot for precise epoxy glue¹ deposition.
4. Employing dynamic dispensing parameters to account for variations in epoxy glue viscosity over time.
5. Continuously monitoring room temperature and relative humidity to ensure consistent bonding quality.



¹ epoxy glue: 3M™ Scotch-Weld™ DP460 [[LINK](#)]

Assembly Procedure

Production step 2: Gas gap production

Adhesive Application

1. Applying epoxy glue on the polycarbonate parts already bonded to the first HPL electrode.

Electrode Placement

2. Carefully positioning and aligning the second HPL electrode on the first electrode to form the gas gap.

Vacuum Bagging

3. Installing the vacuum bagging system to ensure a secure and uniform hold during the epoxy curing process.

Curing Process

4. Curing the epoxy glue for 7 hours at 20–25 °C; maintaining a vacuum level of -200 mbar (i.e. ~ 100 N on each spacer).



Assembly Procedure

Production Step 2: Gas gap production

Gas Pipes Installation

1. Installing and gluing the 3 mm-diameter gas pipes into the polycarbonate lateral profile holes along the short edges.

Edge Sealing

2. Filling and sealing the long edges of the gas volume with the Ethylene Vinyl Acetate (EVA) hot-melt glue².

Spacer Indicators

3. Attaching 0.10 mm thick paper stickers on both gas gap surfaces to mark spacer positions.
3. Fully automated sticker application ensures accurate and consistent placement.






² EVA hot-melt glue: Technicoll® 9310 [\[LINK\]](#)

Gas leak measurement

Objective:

The combined leak rate of the gas volume and gas system is measured by monitoring the drop of internal pressure in order to ensure that gas tightness requirements are met.



Methodology:

- Chamber is pressurized at **3 mbar overpressure** (3x operating pressure for ATLAS RPCs).
- Monitor the drop over **10 minutes**, using a precision pressure gauge.
- Setup is completely automated, in order to improve reliability and production efficiency.

Gas Gap Mechanical Rigidity Test

Objective:



Ensure gas volume integrity by detecting **popped-up spacers** caused by **insufficient adhesive bonding** or **improper handling** during fabrication process.

Methodology:

- Initial Test:** A **laser scan planarity test** is conducted to assess the **flatness** of the gas volume at **atmospheric pressure**.
- Pressurized Test:** The gas volume is then **pressurized to 3 mbar above atmospheric pressure**, and the **laser scan planarity test** is repeated.

Analysis:

Residuals are calculated by comparing the **laser scans** at **atmospheric** and **pressurized conditions** to identify any **discrepancies** indicating **popped-up spacers**.



Mock-up gas volume opening


The mock-up is an accurate representation of the status of the full-scale volume, in terms of detector components, materials, and quality of the coating.

○ Expected visual inspection results:

- The oil coating is applied uniformly across all surfaces.
- The linseed oil has fully polymerized on both HPL plates.
- Minimal dust / debris should be present in the coating.

○ Scratch resistance:


- A 10 mm blade, held at 45°, applying 1 N of force, scrapes the coating for a length of 100 mm.
- No oil residue should be left on the blade, and no damage should be visible on the coating.



Mock-up gas volume opening

The mock-up is an accurate representation of the status of the full-scale volume, in terms of detector components, materials, and quality of the coating.

- Expected visual inspection results:
 - The oil coating is applied uniformly across all surfaces.
 - The linseed oil has fully polymerized on both HPL plates.
 - Minimal dust / debris should be present in the coating.
- Scratch resistance:
 - A 10 mm blade, held at 45°, applying 1 N of force, scrapes the coating for a length of 100 mm.
 - No oil residue should be left on the blade, and no damage should be visible on the coating.



Mock-up gas volume opening

- Hypothesis (R. Cardarelli): residue deposits from epoxy glue outgassing around the spacers interfere with the proper adhesion of the linseed oil layer.



- Epoxy glue used at GTE company: Araldite® 2011.
- Epoxy glue used at MPI and German companies: 3M™ Scotch-Weld™ DP 460.



The halos in gas gaps produced at MPI / German industrial partners are smaller, typically 1- 1.3 cm in diameter.



The 3M™ Scotch-Weld™ DP 460 used by MPI seems to have better outgassing properties.

Compositional analysis planned to study the causes behind the formation of halos.

GTE real-size gas volume opening: L. Pontecorvo [\[LINK\]](#)







Long-Term Stability Test

Objective:

Ensure long-term gas volume stability by continuously monitoring the gas gap current over time with the standard ATLAS RPC gas mixture.

Methodology:




1. The gas gap current is continuously monitored over time at applied voltages of 5.0 kV, 5.4 kV, and 5.8 kV, with each conditioning step lasting 48 hours.
2. The volt-amperometric characteristic curves are measured at both the beginning and the end of the conditioning period.



Long-Term Stability Test

Current in the gas gap is strongly dependent on environmental conditions.

A **second-order correction** [\[LINK\]](#) is applied every measurement cycle, to ensure that the effective (P-T corrected) voltage applied to the gas gap remains within 1% of the desired value.




Improper consideration for environmental parameters could make us reject a good gas gap.

Final certification phase: Longevity Studies




- 1-year long-term irradiation of small- and full-scale RPCs at CERN GIF++ to validate components and production procedures.


real-scale RPCs under irradiation test at GIF++



gas gap current vs. integrated charge



Volt-Amperometric curve vs. integrated charge



- No aging effects observed up to 6 mC/cm² (2% of the RPC operating lifetime under HL-LHC conditions).
- Studies on-going up to 285 mC/cm², corresponding to 10 years of HL-LHC operation with a safety factor of 3.